















## NUMBERS - DATES - FACTS

compli	Dimensions h x w x d [mm]	Tank capacity [l]	Hmax [m]	Qmax [m³/h]	Free passage [mm]	Inlet height [mm]
Single units	'			1		
300 E	445 x 525 x 525	50	10,5	29	50	180
400	445 x 650 x 595	64	7	48	70	180/250
500	600 x 835 x 690	115	20	76	70	variable
100 MultiCut	450 x 500 x 636	38	24	18	7	180/250
500 MultiCut	600 x 835 x 690	115	24	18	7	variable
Duplex units				·		
1000	600 x 835 x 690	115	20	76	70	variable
1200	800 x 910 x 1010	350	20	76	70	560-700
1500	820 x 910 x 1610	500	22	100	70 / 100	700
2500	820 x 1955 x 1610	2 x 500	22	100	70 / 100	700
1000 MultiCut	600 x 835 x 690	115	24	18	7	variable
Stainless steel units						
1200 Stainless steel	880 x 770 x 1142	270	16	122	80 / 100	700
1400 Stainless steel	985 x 970 x 1375	540	16	122	80 / 100	800
1600 Stainless steel	985 x 970 x 1882	900	16	122	80 / 100	800









## PVC inlet sluice valve

DN 100 or DN 150, with pipe sockets bonded in, for the time-saving and space-saving direct connection to the inlet clamping flange.

## COMPLI SEWAGE LIFTING STATIONS - CONVINCING QUALITY

- Ready to plug-in
  - no electrician required
  - also available with swing-type check valve
- Height adjustable clamping flange
  - quick adjustment to suit the wastwater situation on site
- **Easy installation** 
  - due to flexible connection facilities
- Protection from moisture penetration
  - due to moisture sealed cable inlet
- Inlet-optimised tank baseless maintenance required
- Large cleaning opening
  - maintenance-friendly

- Smooth running and quiet
  - due to cast support platform
- Guided float switch
  - for reliable, clearly defined switching points
- ▶ Easy-to-operate controls
  - clear layout of display and control elements
- LGA type tested and monitored
- ▶ All components "Made in Germany"

Further information regarding sewage lifting stations at www.jung-pumpen.de

